



# VR-600A SERIES

## CLASS 600 TRUNNION-MOUNTED FLANGED BALL VALVE

### KEY BENEFITS

- ANSI Class 600 · trunnion mounted
- 3-piece side-entry · A216 WCB body
- ENP ball & metal seats · gear operated



## CLASS 600 TRUNNION-MOUNTED FLANGED BALL VALVE



### OVERVIEW

The Apache VR-600A Series is a Class 600 trunnion-mounted flanged ball valve of three-piece (side-entry) construction for high-pressure pipeline service. A216 WCB left, center, and right bodies carry an electroless-nickel-plated (ENP) ball, stem, and metal seat rings, with integral drain and vent valves and lifting lugs.

### DIMENSIONAL DATA

NPS	DN	D	L	D	D1	D2	B	F	N-Ø
6"	150	5.91	22.00	14.00	11.50	8.50	1.88	0.28	12 × Ø1.12

Dimensions in inches; DN in mm. d = bore · L = face-to-face · D = flange OD · D1 = bolt circle · D2 = raised-face OD · b = flange thickness · f = raised-face height · n-Ø = bolt count × hole dia. Flanges per ANSI Class 600 (ASME B16.5). Additional sizes on request.



### STANDARDS & OPTIONS

<b>Pressure Rating</b>	ANSI Class 600
<b>Design</b>	Trunnion-mounted, 3-piece side-entry
<b>Body</b>	A216 WCB cast steel
<b>Ball / Stem</b>	A105 + ENP
<b>Seat Rings</b>	A105 + ENP (metal seat)
<b>Features</b>	Integral drain & vent valves, lifting lugs
<b>End Connections</b>	ANSI Class 600 flanged (raised face)
<b>Sizes</b>	6"

### MATERIALS / CONSTRUCTION

#	COMPONENT	MATERIAL
1	Left / Right Body	A216 WCB
2	Center Body	A216 WCB
3	Ball	A105 + ENP
4	Stem	A105 + ENP
5	Seat Rings	A105 + ENP
6	Upper Cover	A105 + ENP
7	Lower Cover	Nylon
8	O-Rings / Washers	304 + Graphite / Viton
9	Bolts	A276 410
10	Screws	A276 420 / Inconel X-750
11	Nuts / Springs	A193 B7M
12	Radial Bearing	A276 316 / CS-PTFE
13	Drain & Vent Valves	CS-PTFE / Viton
14	Lifting Lugs	CS + Zn

## QUALITY. INTEGRITY. RELIABILITY.

Engineered solutions for demanding environments.

[www.apachemfg.com](http://www.apachemfg.com)

### GREATER HOUSTON

8809 Bailey Rd  
Manvel, TX 77578  
(713) 941-1669

### ODESSA

2650 West Remington Rd  
Odessa, TX 79763  
(432) 385-7470